

P1 314681

REC'D 12 DEC 2000

WIPO

PGT

# THE UNITED STATES OF AMERICA

**TO ALL TO WHOM THESE PRESENTS SHALL COME:**

**UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office**

3

December 06, 2000

**THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM  
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK  
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT  
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A  
FILING DATE UNDER 35 USC 111.**

**APPLICATION NUMBER: 09/556,086**

**FILING DATE: April 21, 2000**

**PCT APPLICATION NUMBER: PCT/US00/25286**



**By Authority of the  
COMMISSIONER OF PATENTS AND TRADEMARKS**

*M. K. Hawkins*

**M. K. HAWKINS  
Certifying Officer**

**PRIORITY  
DOCUMENT**

**SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)**

04-24-00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Attorney Docket No.: 1702-1-3

04/21/00  
JCS98 U.S. PTO  
09/556086

JCS98 U.S. PTO  
09/556086  
04/21/00

CERTIFICATE OF MAILING OR TRANSMISSION

"Express Mail" mailing label number: EK481647751US

Date of Deposit: April 21, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" under 37 CFR, Section 1.10 on the date indicated above and is addressed to Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231 by

*Stephanie Corp*  
Signature

BOX PATENT APPLICATION  
ASSISTANT COMMISSIONER FOR PATENTS  
WASHINGTON, DC 20231

Sir:

Enclosed for filing is the patent application of:

Inventors: Maxwell J. Wells  
David Waller  
Navdeep S. Dhillon

Title: MUSIC SEARCHING METHODS BASED ON HUMAN PERCEPTION

Including:

- ☒ 1. A specification including claims consisting of 34 pages.
- ☒ 2. Formal drawings consisting of 8 sheets.
- ☒ 3. Declaration and Power of Attorney.

Additionally:

- ☒ 4. An assignment of the invention to CantaMetrix, Inc. is attached.
- ☒ 5. A Verified Statement (Declaration) Claiming Small Entity Status is enclosed.
- ☒ 6. A filing date in accordance with 37 CFR 1.10 is requested (Express mail certificate is part of this transmittal letter).

7.

# COMPUTATION OF FEE


Claims	Number Filed	Number Extra	Basic Fee \$690/\$345
Total	33 - 20 =	13 x \$18/\$9 =	\$117.00
Indep.	7 - 3 =	4 x \$78/\$39 =	\$156.00
Multi Dep.	xxx	xxx	x\$260/\$130 =
TOTAL Filing Fee:			\$618.00

Assignment Recording Fee (\$40.00): \$40.00

- 0955086 1042100
- ☒ 8. Check No. 15236 for \$618.00 for filing fee is enclosed.  
☒ 9. Check No. 15244 for \$40.00 for assignment fee is enclosed.  
☐ 10. No fee is enclosed at this time.  
☒ 11. Charge any additional fees to Deposit Account No. 07-1897.  
☒ 12. A copy of this letter is enclosed.  
☒ 13. A postcard is enclosed as acknowledgment of receipt of this application.

Respectfully submitted,

GRAYBEAL JACKSON HALEY LLP



Jeffrey T. Haley  
Registration No. 34,834  
155-108th Avenue N.E., Suite. 350  
Bellevue, WA 98004-5901  
(425) 455-5575

## MUSIC SEARCHING METHODS BASED ON HUMAN PERCEPTION

5

1.0 BACKGROUND

Modern computers have made possible the efficient assemblage and searching of large databases of information. Text-based information can be searched for key words. Until recently, databases containing recordings of music could only be searched via the textual metadata associated with each recording rather than via the acoustical content of the music itself. The metadata includes information such as title, artist, duration, publisher, classification applied by publisher or others, instrumentation, and recording methods. For several reasons it is highly desirable to be able to search the content of the music to find music which sounds to humans like other music, or which has more or less of a specified quality as perceived by a human than another piece of music. One reason is that searching by sound requires less knowledge on the part of the searcher; they don't have to know, for example, the names of artists or titles. A second reason is that textual metadata tends to put music into classes or genres, and a search in one genre can limit the discovery of songs from other genres that may be attractive to a listener. Yet another reason is that searching by the content of the music allows searches when textual information is absent, inaccurate, or inconsistent.

A company called Muscle Fish LLC in Berkeley, California has developed computer methods for classification, search and retrieval of all kinds of sound recordings. These methods are based on computationally extracting many "parameters" from each sound recording to develop a vector, containing a large number of data points, which characteristically describes or represents the sound. These methods are described in a paper entitled Classification, Search, and Retrieval of Audio by *Erling Wold, Thom Blum, Douglas Keislar, and James Wheaton* which was published in September 1999 on the Muscle Fish website at *Musclefish.com*, and in US Patent 5,918,223 to Blum et al entitled "Method and article of manufacture for content-based analysis, storage, retrieval, and segmentation of audio information."

The Blum patent describes how the authors selected a set of parameters that can be computationally derived from any sound recording with no particular emphasis on



recordings as all comprising a single class as perceived by the human, and the computer system will then derive from these examples appropriate ranges for each parameter to characterize that class of sounds and distinguish it from other classes of sounds in the database. Based on this approach, it is not important that any of the parameters relate to human perception. It is only important that the data within the vectors be capable of distinguishing sounds into classes as classified by humans where music is merely one of the classes.

## 2.0 SUMMARY OF THE INVENTION

The invention builds on the extraction of many parameters from each recording as described by Blum and adds improvements that are particularly adapted to music and to allowing humans to find desired musical recordings within a large database of musical recordings. The invention is a method which performs additional computations with the Blum parameters and other similar parameters to model descriptors of the music based on human perception.

When human listeners compare one recording of music to another, they may use many different words to describe the recordings and compare the differences. There will often be little agreement between the humans as to the meanings of the descriptive words, or about the quantity associated with those words. However, for selected descriptive words, there will often be substantial agreement among large numbers of people.

For example, descriptive terms which immediately achieve substantial agreement among human listeners include: energy level and good/bad for dancing. Other descriptors of music with significant agreement among listeners include: sadness, happiness, anger, symphonicness, relative amount of singer contribution, melodicness, band size, countryness, metallicness, smoothness, coolness, salsa influence, reggae influence and recording quality. Other descriptors which immediately achieve consensus or which achieve consensus over time will be discovered as the methods achieve widespread implementation.

All of the above-mentioned descriptors of music are scalars -- that is, they are one dimensional measures rather than multidimensional vectors of data. Scalars are chosen because most people cannot easily describe or even understand the difference between one multidimensional vector describing a recording of music and another

multidimensional vector describing another recording of music. People tend to express themselves and think in scalars, such as "this recording is better for dancing than that recording." Sometimes they may combine many multi dimensional characteristics into a single category and think and express themselves in a scalar of that category. For  
5 example "this music is more country than that music."

In the methods of the present invention, rather than using a multidimensional vector with large amounts of data extracted from each musical recording, the originally extracted parameter data are mathematically combined with an algorithm that achieves a high correlation with one of the scalars of human perception. Each algorithm is  
10 empirically derived by working with large numbers of recordings and asking a listener, or preferably large numbers of listeners, to place the recordings in relative position compared to each other with respect to a descriptor such as energy level, or any of the above-listed descriptors, or any other descriptor. In other words, the data which is mathematically extracted from the music is further processed based on a computational model of human perception to represent the music as a set of scalars, each of which corresponds as well as possible with human perception.  
15

In the invented methods, parameters such as those used by Blum are first calculated, but then, instead of storing the data of these calculated parameters, the data from the parameters is processed through each one of the algorithms to achieve a single number, a scalar, which represents the music with respect to a particular descriptor based on human perception. This collection of scalars is then stored for each musical recording. In other words, instead of working with a first derivative of data extracted from the original music recordings (the parameters), the invented methods work with a second derivative of data which is extracted from the first derivative of data. Processing through  
20 these algorithms is "lossy" in the sense that the original parameter data cannot be recreated from the set of scalars, just as the first derivative data computations of the parameters are "lossy" because the original music cannot be recreated from the parameter data.  
25

By characterizing each musical recording as a set of scalar descriptors, each of  
30 which is based on human perception, the system allows a human to search for a recording where the descriptors fall within certain ranges or which, compared to a sample recording, has a little bit more or a little bit less, or a lot more or a lot less of any identified scalar characteristic.

00555066-042100

Each algorithm for converting the parameter data, which is a first derivative of the music, into descriptor data, which is a second derivative based on the first derivative, can be of any type. The simplest type of algorithm simply applies a multiplied weighting factor to each data point measured for each parameter and adds all of the results to achieve a single number. However, the weightings need not be linear. Each weighting can have a complex function for producing the desired contribution to the resultant scalar. Each weighting can even be generated from a look-up table based on the value of each parameter datum. What is important is that the algorithm is empirically developed to achieve a high correlation with human perception of the selected descriptor. Of course, the algorithms will constantly be improved over time, as will the parameter extraction methods, to achieve better and better empirical correlation with human perception of the descriptors. Whenever improved extraction algorithms or combinatorial algorithms are ready for use, the set of scalars for each recording in the entire database is recalculated.

If a user wishes to find a recording which is similar to a recording which has not yet been processed into a set of scalar descriptors, the user provides a representative portion of the recording, or directs the system where to find it. The computer system extracts the parameters, combines them according to the algorithms with the appropriate weightings and develops a set of scalars for the recording which are calculated by the same methods as the scalars for recordings in the database. The new recording can then easily be compared to any recording already in the database.

The prior art literature describes many methods for extracting parameters from music. The inventors of these methods often apply labels which correspond somewhat with human perception such as "pitch," or "brightness." However, few of them, or none of them, correlate highly with human perception. In fact, there are many competing methods which yield different results for calculating a parameter with the same label such as "pitch," or "brightness." Although these competing calculation methods were typically derived in an attempt to roughly model human perception based on theories of sound, for most or all of the parameters, human perception can be better modeled by combining the results of several calculation methods in an algorithm with various weightings. This fact of reality is demonstrated by the well known phenomenon that the human ear requires greater amplification of low frequencies and high frequencies to perceive them as the same loudness compared to mid-range frequencies when played



at low volume. It is well known that the best models for human perception of loudness apply a compensating algorithm based on frequency. Of course, loudness is not a meaningful descriptor of music because any musical recording can be played at high volume or low volume and original music can be recorded at high volume or low volume.

5

### 3.0 BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows the prior art method described by Blum.

10

Figure 2 describes the method by which Blum would find sounds that sound alike.

Figure 3 is an illustration of the current invention as it is used to create a database of descriptors of music.

15

Figure 4 illustrates a method for creating and searching a database.

Figure 5 is an example of an interface used to interact with a database.

20

Figure 6 illustrates how the current invention is used to find music that humans perceive as sounding alike using weighted parameters.

Figure 7 illustrates how the current invention is used to find music that humans perceive as sounding alike using weighted descriptors.

25

Figure 8 is a method for determining the perceptual salience of a parameter.

### 4.0 DETAILED DESCRIPTION

#### 4.1 Prior art

30 The prior art method of categorizing sounds, as described by Blum, is illustrated in Figure 1. A database of stored sounds 101 is fed to a parameter extractor 102, where the sounds are decomposed using digital signal processing (DSP) techniques that are known in the art to create parameters 103 such as loudness, brightness, fundamental

frequency, and cepstrum. These parameters are stored as multi-dimensional vectors in an n-dimensional space of parameters 104.

In order to find sounds that are alike, the procedure illustrated in Figure 2 is used. In Phase 1, a human selects a sound, step 202, from a database of stored sounds 201, that falls into a category of sounds. For example, "laughter." This is the target sound. The target sound is fed into a parameter extractor 204 to create a number of parameters 205, with a large number of data points over time for each parameter. The parameters from the sound are then stored as a vector in an n-dimensional space 206.

It is assumed that all sounds within, or close to, the area describing laughter all sound like laughter. One way of exploring this is shown in Phase 2 of Figure 2. The parameter values of the target sound are adjusted, step 207. A new sound is played, step 208, which corresponds with the adjusted parameter values. A human listens to the new sound and determines whether or not the new sound is perceptually similar to the target sound, step 209. If it is not, branch 210, the parameters are again adjusted, step 207, until a similar sound is found, or there are no more sounds. If a similar sound is found, then the parameter values of that sound are used to determine an area of similar sounding sounds.

The prior art puts sounds into classes. This classification is binary. Either something is like the target class or it is not. There is an assumption that mathematical distance of a parameter vector from the parameter vectors of the target class is related to the perceptual similarity of the sounds. Blum claims that this technique works for cataloging transient sounds. However, for music, it is unlikely that the relationship between two parameter vectors would have any relevance to the perceptual relationship of the music represented by those vectors. This is because the parameters bear insufficient relevance to the human perception of music. Also, music cannot be adequately represented with a binary classification system. A music classification system must account for the fact that a piece of music can belong to one of several classes. For example, something may be country with a rock influence. Also, a classification system must account for the fact that a piece of music may be a better or worse example of a class. Some music may have more or less elements of some descriptive element. For example, a piece of music may have more or less energy, or be more or less country than another piece. A set of scalar descriptors allows for more comprehensive and inclusive searches of music.

## 4.2 Current invention, modeling descriptors (Figures 3 and 8)

### 4.2.1 Overview of operation

5           The invention described here is illustrated in Figure 3. A database of stored music 301 is played to one or more humans, step 302, who rate the music on the amount of one or more descriptors. The same music is fed into a parameter extractor 303, that uses methods known in the art to extract parameters 304 that are relevant to the perception of music, such as tempo, rhythm complexity, rhythm strength, brightness,  
10           dynamic range, and harmonicity. Numerous different methods for extracting each of these parameters are known in the art. A model of a descriptor 305 is created by combining the parameters with different weightings for each parameter. The weightings may vary with the value of the parameter. For example, the parameter "brightness" may contribute to a descriptor value only when it is above a threshold or below a threshold or within a range. The model is refined, step 307, by minimizing the difference, calculated  
15           in step 306, between the human-derived descriptor value and the machine-derived value.

          The objective of using human listeners is to create models of their perceptual processes of the descriptors, using a subset of all music, and to apply that model to the categorization of the set of all music.  
20

### 4.2.2 Limitations of the models

The limit on the goodness of the fit of the model (its predictive power) is determined by, among other things:

- 25           (1)    The variability between the human responses, step 302: High variability means that people do not agree on the descriptors and any model will have poor predictive power.
- (2)    The intra-song variability in the set of all music: High variability within a song means that any one part of the song will be a poor representation of  
30           any other part of the same song. This will impede the listeners' task of judging a representative descriptor for that song, resulting in less accurate data and a less accurate model.

0055036-012100

- (3) How well the subset represents the set: The ability to create a model depends on the existence of patterns of parameters in similar songs. If the subset on which the model is based does not represent the patterns that are present in the set, then the model will be incorrect.

5 We can improve the performance of the model by:

(a) Choosing descriptors for which there is low inter-rater variability. Our criterion for selecting descriptors is a minimum correlation coefficient ( $r$ ) of 0.5 between the mean from at least 5 human raters, and the individual scores from those raters.

10 (b) Applying the technique to music which has low intra-song variability (e.g. some Classical music has high variability within a song). One method for determining intra-song variability is to extract parameters from a series of short contiguous samples of the music. If more than half of the parameters have a standard deviation greater than twice the mean, then the song is classified as having high intra-song variability. Similarly, if more than half of the mean parameters of a song lie more than 3 standard deviations from the mean of the population, that song is classified as having high intra-song variability. This excludes less than 1% of all songs.

(c) Using statistical sampling techniques known in the art (for example, for political polling) to ensure that the subset represents the set.

#### 20 4.2.3 Collecting human data

25 The preferred method for collecting human data is to use a panel of ear-pickers who listen to each song and ascertain the quantity of each of several descriptors, using a Lickert scale, which is well known in the art. For example, nine ear-pickers are given a rating scale with a list of descriptors, as shown below:

Rating scales

1. Energy: How much does the song make you want to move or sing?

1	2	3	4	5	6	7	8	9
No movement.	Little movement	Some movement	A lot of movement	Very much movement				
Very light energy	Light energy	Medium energy	High energy	Very high energy				

2. Rhythm salience: What is the relative contribution of the rhythm to the overall sound of the song?

1	2	3	4	5	6	7	8	9
No rhythmic component	Very little rhythm	Moderate rhythm	A lot of rhythm	The song is all rhythm				

3. Melodic salience: What is the relative contribution of the melody (lead singer/lead instrument) to the overall sound of the song?

1	2	3	4	5	6	7	8	9
No melody	Melody is not too important	Melody is moderately important	Melody is quite important	The song is all melody				

4. Tempo: Is the song slow or fast?

1	2	3	4	5	6	7	8	9
Extremely slow	Pretty slow	Moderate tempo	Pretty fast	Extremely fast				

10  
04-2-100

5

These data are analyzed, and only those descriptors for which there is high inter-rater agreement (low variability) are used in the development of the system. For example, the correlations between the mean ratings and the mean of the individual ratings for 7 descriptors are shown in the table below. All of the mean correlation values are above 0.5 and the descriptors anger, danceability, density, energy, happiness, melodic salience, and rhythmic salience are all acceptable for use within the present system.

Pearson correlation							
Mean Subject rating for:	ANGER	DANCE	DENSITY	ENERGY	HAPPY	MELODIC SALIENC E	RHYTH M SALIENC E
with subject 101	0.76	0.74	0.68	0.88	0.83	0.67	0.73
102	0.73		0.74	0.83	0.86	0.67	0.82
103	0.65		0.68	0.85	0.77	0.72	0.30
104	0.56	0.40	0.71	0.77	0.66	0.72	0.63
105	0.75	0.74	0.69	0.85	0.72	0.14	0.37
106	0.70	0.88	0.75	0.88	0.83	0.39	0.87
107	0.69	0.84	0.71	0.81	0.59	0.57	0.74
108	0.63	0.89	0.76	0.89	0.83	0.57	0.86
201	0.82	0.85	0.86	0.81	0.73	0.44	0.83

Mean Correlation values	0.70	0.76	0.73	0.84	0.76	0.54	0.68
Standard Error of Mean	0.03	0.06	0.02	0.01	0.03	0.06	0.07

Another method uses music with known quantities of some descriptor as defined by the purpose to which it is put by the music-buying public, or by music critics. Our technique rank orders the recommended songs by their quantity of the descriptor, either using the values that come with the music, or using our panel of ear-pickers. For example, [www.jamaicans.com/eddyedwards](http://www.jamaicans.com/eddyedwards) features music with Caribbean rhythms that are high energy. Amazon.Com features a mood matcher in which music critics have categorized music according to its uses. For example, for line dancing they recommend the following

- Wreck Your Life* by Old 97's
- The Best Of Billy Ray Cyrus* by Billy Ray Cyrus
- Guitars, Cadillacs, Etc., Etc.* by Dwight Yoakam
- American Legends: Best Of The Early Years* by Hank Williams
- Vol. 1-Hot Country Hits* by Mcdaniel, et al

Another method uses professional programmers who create descriptors to create programs of music for play in public locations. For example, one company has discovered by trial and error the type of music they need to play at different times of the day to energize or pacify the customers of locations for which they provide the ambient music. They use the descriptor "energy," rated on a scale of 1 (low) to 5 (high). We used 5 songs at each of 5 energy levels and in 5 genres (125 songs total), extracted the parameters and created a model of the descriptor "energy" on the basis of the company's human-derived energy values. We then applied that model to 125 different songs and found an 88% match between the values of our machine-derived descriptors and the values from the human-derived descriptors.

#### 4.2.5 Modeling

The preferred method for representing each descriptor uses generalized linear models, known in the art (e.g. McCullagh and Nelder (1989) Generalized Linear Models, Chapman and Hall). For example, the preferred model of "energy" uses linear regression, and looks like this:

$$(1) \quad \text{Energy} = \beta_0 + \beta_1 * \text{Harmonicity} + \beta_2 * \text{DynamicRange} + \beta_3 * \text{Loudness} + \beta_4 * \text{RhythmComplexity} + \beta_5 * \text{RhythmStrength}$$

The preferred weighting values are:

$$\beta_0 = 4.92$$

$$\beta_1 = -1.12$$

$$\beta_2 = -45.09$$

$$\beta_3 = -7.84$$

$$\beta_4 = 0.016$$

$$\beta_5 = 0.001$$

The preferred descriptor model for "happiness" is:

$$(2) \quad \text{Happiness} = \beta_0 + \beta_1 * \text{Articulation} + \beta_2 * \text{Attack} + \beta_3 * \text{NoteDuration} + \beta_4 * \text{Tempo} + \beta_5 * \text{DynamicRangeLow} + \beta_6 * \text{DynamicRangeHigh} + \beta_7 * \text{SoundSaliience} + \beta_8 (\text{Key})$$

The preferred weighting values are:

$$\beta_0 = 6.51$$

$$\beta_1 = -4.14$$

$$\beta_2 = 8.64$$

$$\beta_3 = -15.84$$

$$\beta_4 = 14.73$$

$$\beta_5 = 6.1$$

$$\beta_6 = -8.7$$

$$\beta_7 = 11.00$$

$$\beta_8 = 0 \text{ if no key; } 10 \text{ if minor keys; } 20 \text{ if major keys}$$



It is likely possible to improve each model by adjusting the weighting values  $\beta_0$  to  $\beta_n$ , so that they vary with the input value of the parameter or using different extraction methods for one or more parameters or adding other parameters to the step of extracting parameters.

Another method of optimizing a descriptor model involves using non linear models. For example:

$$(3) \text{ Energy} = F(\beta_1 * \text{tempo}(\beta_2 * \text{tempo} + \beta_3 * \text{sound salience}))$$

where F is the cumulative normal distribution:

$$F(x) = 1/\sqrt{2\pi}\sigma^2 \int_{-\infty}^x e^{-(x-\mu)^2/2\sigma^2} dx$$

$\sigma^2$  = the standard deviation of x

$\mu$  = the mean of x

The values of  $\beta_n$  are set to 1.0. Other values will be substituted as we develop the process.

Yet another method involves using heuristics. For example, if the beats per minute value of a song is less than 60, then the energy cannot be more than some predetermined value.

The output from each descriptor model is a machine-derived descriptor 308. Several such descriptors for each song are stored in a database 309. The presently preferred descriptors for use in the preferred system are:

Energy  
Tempo  
Mood (happiness)  
Mood (anger)  
Danceability

Once the models of the descriptors have been created, using a subset of all available music 301, they are applied to the classification of other music 311. Tests are conducted to determine the fit between the descriptor models derived from the subset of

music and the other music, by substituting some of the other music 311 into the process beginning with the parameter extractor 303. As new music becomes available, a subset of the new music is tested against the models by placing it into the process. Any adjustments of the models are applied to all of the previously processed music, either by reprocessing the music, or, preferably, reprocessing the parameters originally derived from the music. From time to time, a subset of new music is placed into the process at step 301. Thus, any changes in the tastes of human observers, or in styles of music can be measured and accommodated in the descriptor models.

#### 10 4.2.4 Parameter extractors

The following parameter extraction methods are preferred:

**Harmonicity:** Harmonicity is related to the number of peaks in the frequency domain which are an Integer Multiple of the Fundamental (IMF) frequency. The harmonicity value is expressed as a ratio of the number of computed IMFs to a maximum IMF value (specified to be four). Harmonicity values H are computed for time windows of length equal to one second for a total of 20 seconds. Mean and standard deviation values are additional parameters taken over the vector H.

**Loudness:** Loudness is defined to be the root mean square value of the song signal. Loudness values L were computed for time windows of length equal to one second for a total of 20 seconds.

**Dynamic Range:** Standard deviation of loudness for 20 values, calculated 1/second for 20 seconds.

**Rhythm Strength:** Rhythm strength is calculated in the same process used to extract tempo. First, a short-time Fourier transform spectrogram of the song is performed, using a window size of 92.8 ms (Hanning windowed), and a frequency resolution of 10.77 Hz. For each frequency bin in the range of 0-500 Hz, an onset track is formed by computing the first difference of the time history of amplitude in that bin. Large positive values in the onset track for a certain frequency bin correspond to rapid



L:S ratio close to 1.00 reflects legato articulation. Ratios less than 1.00 are considered staccato.

**Attack** is the speed at which a note achieves its half-peak amplitude.

5

**Note Duration** Pitch is extracted by using a peak separation algorithm to find the separation in peaks in the autocorrelation of the frequency domain of the song signal. The peak separation algorithm uses a windowed threshold peak detection algorithm which uses a sliding window and finds the location of the maximum value in each of the peak-containing-regions in every window. A peak-containing-region is defined as a compact set of points where all points in the set are above the specified threshold, and the surrounding points are below the threshold. A confidence measure in the pitch is returned as well; confidence is equal to harmonicity. Pitch values  $P$  are computed for time windows of length equal to 0.1 second. Changes of less than 10 Hz are considered to be one note.

10

15

**Tempo** The tempo extraction technique is described in an earlier section on rhythm strength.

**Dynamic Range Low** Standard deviation of loudness calculated over a duration of 10 seconds.

**Dynamic Range High** Standard deviation of loudness calculated over a duration of 0.1 seconds.

25

**Sound Salience** Uses a modified version of the rhythm extraction algorithm, in which spectral events without rapid onsets are identified.

**Key** Determines the key by the distribution of the notes identified with the note extractor.

30

#### 4.2.6 Optimizing the parameter extractors

Another method for optimizing the fit between the human-derived descriptor value and the machine-derived value is to adjust the extractor performance, step 310. This can be accomplished by using extractors in which some or all of the internal values, for example the sample duration, or the upper or lower bounds of the frequencies being analyzed, are adjusted. The adjustment is accomplished by having an iterative program repeat the extraction and adjust the values until the error, step 306, between the human values and the machine values is minimized.

It is important that the parameters extracted from the music have some perceptual salience. This is tested using the technique illustrated in Figure 8. The parameter extractor 801 is tested, step 802, by visually or audibly displaying the parameter value while concurrently playing the music from which it was extracted. For example, a time history of the harmonic values of a song, sampled every 100 ms, is displayed on a screen, with a moving cursor line. The computer plays the music and moves the cursor line so that the position of the cursor line on the x-axis is synchronized with the music. If the listener or listeners can perceive the correct connection between the parameter value and the changes in the music then the parameter extractor is considered for use in further model development, branch 803. If it is not perceived, or not perceived correctly, then that extractor is rejected or subjected to further improvement, branch 804.

#### 4.3 Interacting with the database (figures 4 and 5)

Once the database of descriptors 309 has been created, it can be combined with other meta data about the music, such as the name of the artist, the name of the song, the date of recording etc. One method for searching the database is illustrated in Figure 4. A large set of music 401, representing "all music" is sent to the parameter extractor 402. The descriptors are then combined with other meta data and pointers to the location of the music, for example URLs of the places where the music can be purchased, to create a database 405. A user can interrogate the database 405, and receive the results of that interrogation using an interface 406.

An example of an interface is illustrated in Figure 5. A user can type in textual queries using the text box 504. For example; "Song title: Samba pa ti, Artist: Santana." The user then submits the query by pressing the sort by similarity button 503. The song

"Samba pa ti" becomes the target song, and appears in the target box 501. The computer searches the n dimensional database 405 of vectors made up of the song descriptors, looking for the smallest vector distances between the target song and other songs. These songs are arranged in a hit list box 502, arranged in increasing vector distance (decreasing similarity). An indication of the vector distance between each hit song and the target song is shown beside each hit song, expressed as a percent, with 100% being the same song. For example, the top of the list may be "Girl from Ipanema by Stan Getz, 85%."

Another type of query allows a user to arrange the songs by profile. First, the user presses the sort by number button 509 which lists all of the songs in the database in numerical order. The user can scroll through the songs using a scroll bar 506. They can select a song by clicking on it, and play the song by double clicking on it. Any selected song is profiled by the slider bars 505. These show the scalar values of each of several descriptors. The current preferred method uses energy, danceability and anger. Pressing the sort by profile button 510 places the highlighted song in the target box 501 and lists songs in the hit box 503 that have the closest values to the values of the target song.

Yet another type of query allows the user to sort by similarity plus profile. First a target song is chosen and the songs in the hit box 502 are listed by similarity. Then the user performs a search of this subset of songs by using the slider bars 505. For example, the slider values of the original target song are 5,6,7 for energy, danceability and anger respectively. The user increases the energy value from 5 to 9 and presses the search similar songs button 507. The profile of the target song remains as a ghosted image 508 on the energy slider. The computer searches the subset of songs for a song with values of 9, 6 and 7. Songs with that profile are arranged in decreasing order of similarity. Songs without that profile are appended, arranged by decreasing similarity. The target song remains in the target box 501. A user can choose a new target song by clicking on a song in the hit list box 502.

#### 4.4. Modelling likeness with parameters (Figure 6)

Figure 6 illustrates how the invention is used to find music that sounds to human listeners like any musical composition selected by a user. The processes in Figure 3 are

repeated to create a set of parameters 604. These are used to create a model of likeness 605 by a process described below.

#### 4.4.1 Collecting human data

5 One or more humans listen to pairs of songs and judge their similarity on a scale, for example from 1 to 9, where 1 is very dissimilar, and 9 is very similar, step 602.

The objective of using human listeners is to create a model of their perceptual process of "likeness", using a subset of all music, and to apply that model to the set of all music.

10 The preferred method for collecting human data is to use a panel of ear-pickers who listen to pairs of songs and score their similarity, using a Lickert scale, which is well known in the art.

Another method is to have people visit a web site on which they can listen to pairs of songs and make similarity judgments. These judgments could be on a scale of 1 to 9, or could be yes/no. It is possible to estimate a scalar value of similarity based on a large number of binary judgments using statistical techniques known in the art.

#### 4.4.2 Creating the likeness model

15 The objective of the model is to predict these perceived differences using the extracted parameters of music. To build the model, a list of numbers is calculated for the comparison of each song to each other song. The list of numbers consists of a value for each parameter where the value is the difference between the parameter value for a first song and the value of the same parameter for a second song. When the model is used to compare one song to another for likeness, the list of parameter differences between  
20 the two songs is calculated and these differences are the inputs to the model. The model then yields a number that predicts the likeness that people would judge for the same two songs. The model processes the list of difference values by applying weights and heuristics to each value.

25 The preferred method of creating a model of likeness is to sum the weighted parameter values. For example, for three parameters, A, B and C, the following steps are used for songs 1 and 2:

STEP 1 – subtract the parameters of each song

$$A_1 - A_2, B_1 - B_2, C_1 - C_2$$

STEP 2 – calculate the absolute differences. Our preferred method uses a value of  $n = 2$ , but other values can be used.

$$\sqrt[n]{(A_1 - A_2)^n}, \sqrt[n]{(B_1 - B_2)^n}, \sqrt[n]{(C_1 - C_2)^n}$$

STEP 3 – weight and sum the differences. The values of the weights ( $\beta_1 - \beta_n$ ) are determined by linear regression, as explained below.

$$\text{Likeness} = \beta_1 * A_{\text{difference}} + \beta_2 * B_{\text{difference}} + \beta_3 * C_{\text{difference}}$$

The value of the weights are determined by a process of linear regression, step 608, which seeks to minimize the difference, step 606, between the human-derived likeness values, step 602, and the output from the model, 605. The preferred model of likeness is:

$$(4) \quad \text{Likeness} = \beta_0 + \beta_1 * \text{mean loudness} + \beta_2 * \text{rhythm strength} + \beta_3 * \text{tempo} + \beta_4 * \text{dynamic range} + \beta_5 * \text{mean brightness} + \beta_6 * \text{mean harmonicity} + \beta_7 * \text{rhythm complexity} + \beta_8 * \text{standard deviation brightness} + \beta_9 * \text{standard deviation harmonicity}$$

Where

$$\beta_0 = 0$$

$$\beta_1 = -0.108$$

$$\beta_2 = -0.225$$

$$\beta_3 = -0.127$$

$$\beta_4 = -0.015$$

$$\beta_5 = -0.296$$

$$\beta_6 = -0.223$$

$$\beta_7 = -0.122$$

$$\beta_8 = 0.277$$

$$\beta_9 = -0.074$$

Another method for deriving likeness is to calculate the correlation coefficients ( $r$ ) of the parameter values between each pair of songs in the database, and to create a matrix of similarity for the songs, with high correlation equating to high similarity. The parameter values are normalized to ensure that they all have the same range. Song 1



provides the parameters for the x values, and song 2 provides the parameters for the y values in the following formula:

$$r = \frac{\sum (x_i - x_{\text{mean}}) (y_i - y_{\text{mean}})}{\sqrt{[\sum (x_i - x_{\text{mean}})^2] [\sum (y_i - y_{\text{mean}})^2]}}$$

5 Where  $x_{\text{mean}}$  and  $y_{\text{mean}}$  are the means of the normalized parameter values for songs 1 and 2.

10 The rationale behind using correlation coefficients is that if the parameters of two songs have a high positive correlation which is statistically significant then the two songs will be judged to be alike.

#### 4.4.3 Organizing and storing the likeness data

15 The preferred method of storing and organizing the parameter differences data is as a multi dimensional vector in a multi dimensional database 607. The resulting matrix contains  $n*(n-1)/2$  cells where n is the number of songs. The model is used by starting with a target song 609, calculating the difference in value for each parameter between the comparison song and the songs in the target database, steps 603 - 605, and then applying the model to the difference values to arrive at a value which represents the likeness between the comparison song and each song in the target database.

20 An alternative method precomputes the 2 dimensional similarity matrix such that each song is connected with only those songs with which there is a match above a predetermined value. Thus, the low matching songs are culled from the similarity matrix. This decreases the size of the database and can increase the search speed.

#### 25 4.4.4 Limitations of the model

The limit on the goodness of the fit of the model (its predictive power) is determined by, among other things:

- 30
- (1) The variability between the human responses, step 602. High variability means that people do not agree on the descriptors and any model will have poor predictive power.
  - (2) The intra song variability in the set of all music. High variability within a song means that any one part of the song will be a poor representation of any

other part of the same song. This will impede the listeners' task of judging similarity between such songs, resulting in less accurate data and a less accurate model.

- (3) How well the subset represents the set. The ability to create a model depends on the existence of patterns of parameters in similar songs. If the subset on which the model is based does not represent the patterns that are present in the set, then the model will be incorrect.

We have found that a group of 12 human observers had a correlation coefficient of 0.5 or greater in what they consider sounds alike. This indicates that there is sufficient inter-rater reliability to be able to model the process. We can further improve our chances of successfully using the model to predict what sounds alike by:

- (a) Only applying the technique to music which has low intra-song variability (e.g. some Classical music has high variability within songs).  
(b) Using statistical sampling techniques known in the art (for example, for political polling) to ensure that the subset represents the set.

#### **4.5 Modeling likeness with descriptors (Figure 7)**

Figure 7 illustrates an alternative method for finding music that sounds to human listeners like any musical composition selected by a user. The processes in Figure 3 are repeated to create a set of descriptors 706. These are used to create a model of likeness 707 by a process similar to that used to create the model of likeness using parameters 605.

##### **4.5.1 Collecting human data**

One or more humans listen to pairs of songs and judge their similarity on a scale, for example from 1 to 9, where 1 is very dissimilar, and 9 is very similar, step 702. The objective of using human listeners is to create a model of their perceptual process of "likeness", using a subset of all music, and to apply that model to the set of all music. The preferred or alternative methods of collecting human data described with Figure 6 are used.

#### 4.5.2 Creating the likeness model

The objective of the model is to predict the perceived differences using the modelled descriptors of music. To build the model, a list of numbers is calculated for the comparison of each song to each other song. The list of numbers consists of a value for each descriptor where the value is the difference between the descriptor value for a first song and the value of the same descriptor for a second song. When the model is used to compare one song to another for likeness, the list of descriptor differences between the two songs is calculated and these differences are the inputs to the model. The model then yields a number that predicts the likeness that people would judge for the same two songs. The model processes the list of descriptor difference values by applying weights and heuristics to each value.

The preferred method of creating a model of likeness is to sum the weighted descriptor difference values. For example, for three descriptors, A, B and C, the following steps are used for songs 1 and 2:

STEP 1 – subtract the descriptors of each song

$$A_1 - A_2, B_1 - B_2, C_1 - C_2$$

STEP 2 – calculate the absolute differences. Our preferred method uses a value of  $n = 2$ , but other values can be used.

$$n\sqrt{(A_1 - A_2)^n}, n\sqrt{(B_1 - B_2)^n}, n\sqrt{(C_1 - C_2)^n}$$

STEP 3 – weight and sum the differences. The values of the weights ( $\beta_1 - \beta_n$ ) are determined by linear regression, as explained below.

$$\text{Likeness} = \beta_1 * A_{\text{difference}} + \beta_2 * B_{\text{difference}} + \beta_3 * C_{\text{difference}}$$

The value of the weights are determined by a process of linear regression, step 710, which seeks to minimize the difference, step 708, between the human-derived likeness values, step 702, and the output from the model. The preferred model of likeness is:

$$(5) \quad \text{Likeness} = \beta_0 + \beta_1 * \text{Energy} + \beta_2 * \text{Tempo} + \beta_3 * \text{Happiness} + \beta_4 * \text{Anger} + \beta_5 * \text{Danceability}$$

$$\beta_0 = 0$$

$$\beta_1 = 11.4$$



The likeness database may be quickly searched by starting with any song and immediately finding the closest songs. A more enhanced search combines a similarity search with a descriptor search and the descriptor adjustment step described above.

The steps are:

- 5      1a. Find a list of likeness matches, including some that are somewhat different
- 1b. Present only the acceptable likeness songs.
2. When a search adjusted by a scalar descriptor is requested, rank the entire
- list of likeness matches (1a) by the descriptor to be adjusted.
3. Present a new list based on the adjusted values with the best matches at the
- 10      top.

This means that the likeness list (1a.) compiled for the original search is much broader than the list displayed for the user(1b), and includes songs that are less similar to the initial target song than would be tolerated by the listener. These poorer likeness matches lie below the presentability threshold for the initial target.

005508E-04-2100  
15

What is claimed is:

- 5
1. A method for building a computational model of human perception of a descriptor of music, comprising:
- 10
- a) extracting from each of at least 5 electronic representations of musical recordings at least two numeric parameters;
- b) for each recording, combining the numeric parameters with a weighting for each parameter to compute a single number representing the descriptor for that recording;
- 15
- c) adjusting the weightings for the parameters to find a set of weightings where each computed descriptor for each recording most closely matches perceptions reported for the recording by one or more human listeners.
2. A computer readable medium containing a computer program which causes a computer to perform the method of claim 1.
- 20
3. A method for generating a data record associated with a music recording, the record comprising two or more scalar descriptors, each descriptor numerically describing the recording of music with which the data record is associated, comprising:
- a) extracting from an electronic representation of the recording of music at least two numeric parameters;
- b) combining the numeric parameters with a weighting for each parameter to compute a single number representing the descriptor for that recording, where the weightings were previously determined by:
- 25
- c) extracting from an electronic representation of each of at least 5 musical recordings the same at least two numeric parameters;
- d) for each recording, combining the numeric parameters with a weighting for each parameter to compute a single number representing the descriptor for that recording;

00550000-042100

- e) adjusting the weightings for the parameters to find a set of weightings where each computed descriptor for each recording most closely matches perceptions reported for the recording by one or more human listeners.
4. A computer readable medium containing a computer program which causes a computer to perform the method of claim 3.
5. A computer readable medium containing a computer extracted data record associated with a music recording, the record comprising:
- two or more scalar descriptors, each descriptor numerically describing the recording of music with which the data record is associated, where each descriptor was generated by:
- a) extracting from an electronic representation of the recording of music at least two numeric parameters;
- b) combining the numeric parameters with a weighting for each parameter to compute a single number representing the descriptor for that recording, where the weightings were previously determined by:
- c) extracting from an electronic representation of each of at least 5 musical recordings the same at least two numeric parameters;
- d) for each recording, combining the numeric parameters with a weighting for each parameter to compute a single number representing the descriptor for that recording;
- e) adjusting the weightings for the parameters to find a set of weightings where each computed descriptor for each recording most closely matches perceptions reported for the recording by one or more human listeners.
6. A method for searching a database of data records associated with music recordings to find a desired recording, comprising:
- a) identifying a comparison data record associated with a music recording in a computer readable database containing a plurality of data records, each associated with a music recording, the data records each comprising two





001-240-980530  
0056086-042100

- 5
- a) extracting from each of at least 5 electronic representations of musical recordings at least two numeric parameters;
  - b) receiving from one or more human listeners who compare pairs of the musical recordings an indication of the human's perception of likeness for each compared pair of recordings;
  - c) for each compared pair of the recordings, comparing each numeric parameter of one recording in the pair with the corresponding parameter of the second recording of the pair using an algorithm which produces a parameter comparison number representing the parameter comparison;
- 10
- d) for each compared pair of the recordings, combining the parameter comparison numbers with a weighting for each parameter comparison number to compute a single difference number representing the difference between the two recordings of the pair;
  - e) adjusting the weightings for the comparison numbers to find a set of weightings where each computed difference number for each pair of recordings most closely matches perceptions reported for the pair of recordings by the one or more human listeners.
- 15
11. The method of claim 10 where the algorithm includes subtraction of parameter values.
- 20
12. The method of claim 10 where the algorithm includes computing a correlation between parameter values.
13. The method of claim 10 where, prior to the step of comparing the numeric parameters:
- 25
- a) the parameters for each recording are combined with a weighting for each parameter to compute a single number representing a descriptor for that recording, where
  - b) the weightings were previously determined by adjusting the weightings to find a set of weightings where each computed descriptor for each recording most closely matches perceptions reported for the recording by one or more human listeners, and
- 30

00556095-042100

- c) the descriptors are then used in the step of comparing the numeric parameters in place of the parameters.
14. A computer readable medium containing a computer program which causes a computer to perform the method of claim 10.
- 5 15. A computer readable medium containing a computer program which causes a computer to perform the method of claim 11.
16. A computer readable medium containing a computer program which causes a computer to perform the method of claim 12.
17. A computer readable medium containing a computer program which causes a computer to perform the method of claim 13.
- 10 18. A method for creating a database of differences between music recordings, comprising:
- a) associating an identifier with each recording of a plurality of music recordings;
- b) extracting from each recording of the plurality or recordings at least two numeric parameters;
- c) computing from the extracted parameters for each of a plurality of pairs of the recordings a number which represents the difference between the recordings of the pair; and
- d) assembling the computed difference numbers into a database where each computed difference is associated with the identifier for each of the two recordings from which the difference was computed.
- 15 19 The method of claim 18 where the computing step includes subtraction of parameter values.
- 20 20 The method of claim 18 where the computing step includes computing a correlation between parameter values.
- 21 21 The method of claim 18 where the algorithm used to compute numbers which represent differences between pairs of recordings is empirically developed based on perceptions reported by one or more human listeners.

22. A computer readable medium containing a computer program which causes a computer to perform the method of claim 18.
23. A computer readable medium containing a computer program which causes a computer to perform the method of claim 19.
- 5 24. A computer readable medium containing a computer program which causes a computer to perform the method of claim 20.
25. A computer readable medium containing a computer program which causes a computer to perform the method of claim 21.
- 26 A method for finding a music recording which is perceived by humans to be like  
10 another music recording, comprising:
- a) receiving a specification of a target music recording; and
  - b) searching a database containing computed difference numbers between the target recording and a plurality of other recordings for those recordings which have a small computed difference number from the target music recording.
- 15 27. The method of claim 26 where the database is created by:
- a) associating an identifier with each recording of a plurality of music recordings;
  - b) extracting from each recording of the plurality or recordings at least two numeric parameters;
  - c) computing from the extracted parameters for pairs of the recordings a number which represents the difference between the recordings of the pair; and
  - d) assembling the computed difference numbers into a database where each  
20 computed difference is associated with the identifier for each of the two recordings from which the difference was computed.
- 25 28. The method of claim 27 where the step of computing numbers which represent differences between pairs of recordings is empirically developed based on perceptions of one or more human listeners.

00556036-042100

29. The method of claim 28 where the step of computing a number which represents the difference between the recordings of a pair of recordings includes the intermediate steps of:
- 5 a) combining the parameters for each recording with a weighting for each parameter to compute a single number representing a descriptor for that recording, where
- 10 b) the weightings were previously determined by adjusting the weightings to find a set of weightings where each computed descriptor for each recording most closely matches perceptions reported for the recording by one or more human listeners, and
- c) the descriptors are then used in place of the parameters to compute a number which represents the difference between the recordings of the pair.
- 15 30. A computer readable medium containing a computer program which causes a computer to perform the method of claim 26.
31. A computer readable medium containing a computer program which causes a computer to perform the method of claim 27.
32. A computer readable medium containing a computer program which causes a computer to perform the method of claim 28.
- 20 33. A computer readable medium containing a computer program which causes a computer to perform the method of claim 29.

## ABSTRACT

A method for characterizing a musical recording as a set of scalar descriptors, each of which is based on human perception. A group of people listens to a large number of musical recordings and assigns to each one many scalar values, each value describing a characteristic of the music as judged by the human listeners. Typical scalar values include energy level, happiness, danceability, melodiousness, tempo, and anger. Each of the pieces of music judged by the listeners is then computationally processed to extract a large number of parameters which characterize the electronic signal within the recording. Algorithms are empirically generated which correlate the extracted parameters with the judgments based on human perception to build a model for each of the scalars of human perception. These models can then be applied to other music which has not been judged by the group of listeners to give to each piece of music a set of scalar values based on human perception. The set of scalar values can be used to find other pieces that sound similar to humans or vary in a dimension of one of the scalars.

0056085-042100

PATENT

DECLARATION AND POWER OF ATTORNEY  
IN PATENT APPLICATION

Attorney Docket No.: 1702-1-3

As a below named inventor, I hereby declare:

My residence, post office address and citizenship are as stated below next to my name.

I believe that I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are listed below) of the subject matter that is claimed and for which a patent is sought on the invention entitled:

MUSIC SEARCHING METHODS BASED ON HUMAN PERCEPTION

the specification of which

☐ is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim the benefit under Title 35, United States Code Section 119(e) of any United States provisional application(s) listed below.

Application No.

Filing Date

60/153,768

September 14, 1999

I hereby appoint the attorneys associated with Customer No. 000996 to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith. Address all correspondence and phone calls to:

Jeffrey T. Haley  
GRAYBEAL JACKSON HALEY LLP

09556085-042100

155 - 108th Avenue NE, Suite 350  
Bellevue, WA 98004-5901 USA  
Telephone (425) 455-5575  
Facsimile (425) 455-1046

I hereby further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Maxwell J. Wells UK  
Full Name of Inventor Citizenship

6817 - 44<sup>th</sup> Avenue Northeast, Seattle, Washington 98115  
Residence

M. Wells 4/18/00  
Inventor's Signature Date

David Waller USA  
Full Name of Inventor Citizenship

7634 Hollister Ave., #351, Goleta CA 93117  
Residence

\_\_\_\_\_  
Inventor's Signature Date

Navdeep S. Dhillon USA  
Full Name of Inventor Citizenship

8011 - 29<sup>th</sup> Avenue Northwest, Seattle, Washington 98117  
Residence

Navdeep S. Dhillon 4/4/2000  
Inventor's Signature Date

00556086-042100

155 - 108th Avenue NE, Suite 350  
Bellevue, WA 98004-5901 USA  
Telephone (425) 455-5575  
Facsimile (425) 455-1046

I hereby further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.


Maxwell J. Wells \_\_\_\_\_ UK  
Full Name of Inventor \_\_\_\_\_ Citizenship

6817 - 44<sup>th</sup> Avenue Northeast, Seattle, Washington 98115  
Residence \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_

David Waller \_\_\_\_\_ USA  
Full Name of Inventor \_\_\_\_\_ Citizenship

7634 Hollister Ave., #351, Goleta CA 93117  
Residence \_\_\_\_\_

 \_\_\_\_\_ 29 MARCH 00  
Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_

Navdeep S. Dhillon \_\_\_\_\_ USA  
Full Name of Inventor \_\_\_\_\_ Citizenship

8011 - 29<sup>th</sup> Avenue Northwest, Seattle, Washington 98117  
Residence \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_



VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS  
(37 CFR 1.9(f) AND 1.27(c)) - SMALL BUSINESS CONCERN

☐ Applicant(s) or ☐ Patentee(s): Maxwell J. Wells, David Waller, and Navdeep S. Dhillon

☐ Application or ☐ Patent No.: \_\_\_\_\_ Docket No.: 1702-1-3

Title: MUSIC SEARCHING METHODS BASED ON HUMAN PERCEPTION

I hereby declare that I am

☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN CantaMetrix, Inc.

ADDRESS OF CONCERN 110 110<sup>th</sup> Avenue NE Suite 690

Bellevue, Washington 98004

I hereby declare that the above-identified small business qualifies as a small business concern as defined in 13 CFR §121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party of parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in

☒ the specification filed herewith with the title as listed above.

If the rights held by the above-identified small business concern are not exclusive, each

which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

\*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27).

FULL NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING Maxwell J. Wells

TITLE CHIEF TECHNOLOGY OFFICER, CHAIRMAN

SIGNATURE M. Wells DATE 3/27/00




Figure 1

09556085-042100




Figure 2

09556086-042100




Figure 3

0955085-042100




Figure 4

0955085-042100




Figure 5

09556086.042100




Figure 6

09556086.042.100






Figure 7

0955085-042100




Figure 8

09556086-042100